



# ***PRODUCT OVERVIEW***





# MFX-2725 OB

## MFX-2725

### COPY

RADF	50 pages (A5-A3, 52-105 g/m <sup>2</sup> )
Resolution	600 x 600 dpi
Zoom ratio	25-400% (FBS, 1% steps)
FCOT (First Copy Output Time)	5.6 seconds* <sup>1</sup>

### PRINT

Print controller	Standard: GDI, Option: PCL6/5e
Resolution	600 x 600 dpi
Operating System	Windows 98(ethernet only), 98SE, ME, NT4.0(ethernet only), 2000, XP, Server2003 (network print only)* <sup>2</sup> , Vista

### SCAN

Scan speed	0.8 seconds/page
Scan interface	Standard: TWAIN, Option: Ethernet
Duplexscan	Standard automatic
Resolution	600 / 300 / 200 dpi
Scan format	TIFF, PDF
Scan to E-Mail	Option with OfficeBridge
Scan to Folder	Option with OfficeBridge

### FAX

Modem speed	33.6 Kbps
Transmission speed	2 seconds
Memory	64 MB (4,665 A4 pages)* <sup>3</sup>
Memory backup	72 hours
Address book	200 addresses
Group Dialing	32 groups
Broadcasting	230 addresses

- A3 Max. Copy / Print size
- 27 ppm
- 20 ppm with duplex
- LED
- Platen
- 1,000 sheet standard paper capacity (A5-A3, 60-90 g/m<sup>2</sup>)
- 100 sheet bypass (A6-A3, 60-120 g/m<sup>2</sup>)
- Max.: 4 x 500 sheets
- 15 sec. warm up time
- LCD partial Touch Display
- Quad Access
- Standard USB interface, Option: Ethernet
- Voice Guidance

**Office**  
**Bridge**

OfficeBridge Features

- Network Printer
- Scan to Folder
- Scan to E-Mail
- Network PC-Fax
- Fax Forwarding
- 2,000 addresses in address book
- LDAP compliance
- Workflow Management

\*<sup>1</sup> From FBS from 1st cassette \*<sup>2</sup> Utilities (InfoMonitor etc) are not supported.

\*<sup>3</sup> Based on ITU-T Test Document 1 stored at normal resolution.



# MFX-2700 OB

## MFX-2700

### **COPY**

ADF	50 pages (A5-A3, 52-105 g/m <sup>2</sup> )
Resolution	600 x 600 dpi
Zoom ratio	25-400% (FBS, 1% steps)
FCOT (First Copy Output Time)	5.6 seconds* <sup>1</sup>

### **PRINT**

Print controller	Standard: GDI, Option: PCL6/5e
Resolution	600 x 600 dpi
Operating System	Windows 98(ethernet only), 98SE, ME, NT4.0(ethernet only), 2000, XP, Server2003 (network print only)* <sup>2</sup> , Vista

### **SCAN**

Scan speed	0.8 seconds/page
Scan interface	Standard: TWAIN, Option: Ethernet
Duplexscan	Manual (create 2 to 2 copy)
Resolution	600 / 300 / 200 dpi
Scan format	TIFF, PDF
Scan to E-Mail	Option with OfficeBridge
Scan to Folder	Option with OfficeBridge

### **FAX**

Modem speed	33.6 Kbps
Transmission speed	2 seconds
Memory	64 MB (4,665 A4 pages)* <sup>3</sup>
Memory backup	72 hours
Address book	200 addresses
Group Dialing	32 groups
Broadcasting	230 addresses

- A3 Max. Copy / Print size
- 27 ppm
- 20 ppm with duplex
- LED
- Platen
- 1,000 sheet standard paper capacity (A5-A3, 60-90 g/m<sup>2</sup>)
- 100 sheet bypass (A6-A3, 60-120 g/m<sup>2</sup>)
- Max.: 4 x 500 sheets
- 15 sec. warm up time
- LCD partial Touch Display
- Quad Access
- Standard USB interface, Option: Ethernet
- Voice Guidance

**Office**  
**Bridge**

OfficeBridge Features

- Network Printer
- Scan to Folder
- Scan to E-Mail
- Network PC-Fax
- Fax Forwarding
- 2,000 addresses in address book
- LDAP compliance
- Workflow Management

\*<sup>1</sup> From FBS from 1st cassette \*<sup>2</sup> Utilities (InfoMonitor etc) are not supported.

\*<sup>3</sup> Based on ITU-T Test Document 1 stored at normal resolution.



# MFX-2225 OB

## MFX-2225

### **COPY**

RADF	50 pages (A5-A3, 52-105 g/m <sup>2</sup> )
Resolution	600 x 600 dpi
Zoom ratio	25-400% (FBS, 1% steps)
FCOT (First Copy Output Time)	5.6 seconds* <sup>1</sup>

### **PRINT**

Print controller	Standard: GDI, Option: PCL6/5e
Resolution	600 x 600 dpi
Operating System	Windows 98(ethernet only), 98SE, ME, NT4.0(ethernet only), 2000, XP, Server2003 (network print only)* <sup>2</sup> , Vista

### **SCAN**

Scan speed	0.8 seconds/page
Scan interface	Standard: TWAIN, Option: Ethernet
Duplexscan	Standard automatic
Resolution	600 / 300 / 200 dpi
Scan format	TIFF, PDF
Scan to E-Mail	Option with OfficeBridge
Scan to Folder	Option with OfficeBridge

### **FAX**

Modem speed	33.6 Kbps
Transmission speed	2 seconds
Memory	64 MB (4,665 A4 pages)* <sup>3</sup>
Memory backup	72 hours
Address book	200 addresses
Group Dialing	32 groups
Broadcasting	230 addresses

- A3 Max. Copy / Print size
- 22 ppm
- 18 ppm with duplex
- LED
- Platen
- 500 sheet standard paper capacity (A5-A3, 60-90 g/m<sup>2</sup>)
- 100 sheet bypass (A6-A3, 60-120 g/m<sup>2</sup>)
- Max.: 4 x 500 sheets
- 15 sec. warm up time
- LCD partial Touch Display
- Quad Access
- Standard USB interface, Option: Ethernet
- Voice Guidance

**Office**  
**Bridge**

OfficeBridge Features

- Network Printer
- Scan to Folder
- Scan to E-Mail
- Network PC-Fax
- Fax Forwarding
- 2,000 addresses in address book
- LDAP compliance
- Workflow Management

\*<sup>1</sup> From FBS from 1st cassette \*<sup>2</sup> Utilities (InfoMonitor etc) are not supported.

\*<sup>3</sup> Based on ITU-T Test Document 1 stored at normal resolution.



# MFX-2200 OB

## MFX-2200

### COPY

ADF	50 pages (A5-A3, 52-105 g/m <sup>2</sup> )
Resolution	600 x 600 dpi
Zoom ratio	25-400% (FBS, 1% steps)
FCOT (First Copy Output Time)	5.6 seconds* <sup>1</sup>

### PRINT

Print controller	Standard: GDI, Option: PCL6/5e
Resolution	600 x 600 dpi
Operating System	Windows 98(ethernet only), 98SE, ME, NT4.0(ethernet only), 2000, XP, Server2003 (network print only)* <sup>2</sup> , Vista

### SCAN

Scan speed	0.8 seconds/page
Scan interface	Standard: TWAIN, Option: Ethernet
Duplexscan	Manual (create 2 to 2 copy)
Resolution	600 / 300 / 200 dpi
Scan format	TIFF, PDF
Scan to E-Mail	Option with OfficeBridge
Scan to Folder	Option with OfficeBridge

### FAX

Modem speed	33.6 Kbps
Transmission speed	2 seconds
Memory	64 MB (4,665 A4 pages)* <sup>3</sup>
Memory backup	72 hours
Address book	200 addresses
Group Dialing	32 groups
Broadcasting	230 addresses

- A3 Max. Copy / Print size
- 22 ppm
- 18 ppm with duplex
- LED
- Platen
- 500 sheet standard paper capacity (A5-A3, 60-90 g/m<sup>2</sup>)
- 100 sheet bypass (A6-A3, 60-120 g/m<sup>2</sup>)
- Max.: 4 x 500 sheets
- 15 sec. warm up time
- LCD partial Touch Display
- Quad Access
- Standard USB interface, Option: Ethernet
- Voice Guidance

**Office**  
**Bridge**

OfficeBridge Features

- Network Printer
- Scan to Folder
- Scan to E-Mail
- Network PC-Fax
- Fax Forwarding
- 2,000 addresses in address book
- LDAP compliance
- Workflow Management

\*<sup>1</sup> From FBS from 1st cassette \*<sup>2</sup> Utilities (InfoMonitor etc) are not supported.

\*<sup>3</sup> Based on ITU-T Test Document 1 stored at normal resolution.



# MFX-2050 MFX-1450

## COPY

ADF	80 pages (A5-A4, 52-105 g/m <sup>2</sup> )
Resolution	600 x 600 dpi
Zoom ratio	25-400% (FBS)
FCOT (First Copy Output Time)	10/12 seconds* <sup>1</sup>

## PRINT

Print controller	Standard: GDI, Option: PCL6/5e
Resolution	600 x 600 dpi
Operating System	Windows 98(ethernet only), 98SE, ME, NT4.0(ethernet only), 2000, XP, Server2003 (network print only)* <sup>2</sup> , Vista

## SCAN

Scan speed	Mono: 3.2 seconds Colour: 8.1 seconds
Scan interface	Standard: TWAIN, Ethernet
Duplexscan	Manual (create 2 to 2 copy)
Resolution	600 / 300 / 200 / 100* <sup>3</sup> dpi
Scan format	TIFF, PDF, JPEG* <sup>3</sup>
Scan to E-Mail	Standard
Scan to Folder	Standard
Scan to FTP	Standard

## FAX

Modem speed	33.6 Kbps
Transmission speed	2 seconds
Memory	8 MB (650 A4 pages)* <sup>4</sup> Max.: 40 MB (3,370 A4 pages)* <sup>4</sup>
Memory backup	72 hours
Address book	1,000 addresses
Group Dialing	100 groups
Broadcasting	1,030 addresses

- A4 Max. Copy / Print size
- 19/13 ppm
- 10/8 ppm with duplex
- LED
- Platen
- 500 sheet standard paper capacity (A5-A4, 60-90 g/m<sup>2</sup>)
- 50 sheet bypass (A6-A4, 60-120 g/m<sup>2</sup>)
- Max.: 2 x 500 sheets
- 23 sec. warm up time
- Large Touch Display
- Quad Access
- Standard USB and Ethernet interface



### Network Gateway Platform Features

- Network Printerer
- Print on demand
- Security print
- Colour Scan to Colour Printer (create Colour Copies)
- Scan to Folder
- Scan to E-Mail
- Scan to FTP
- Network PC-Fax
- LDAP compliance
- Workflow Management

\*<sup>1</sup> From FBS with 1st cassette selection. \*<sup>2</sup> Utilities (InfoMonitor etc) are not supported.

\*<sup>3</sup> Colour scan only. \*<sup>4</sup> Based on ITU-T Test Document 1 stored at normal resolution.



# MFX-1930 OB

## MFX-1930

### **COPY**

ADF	80 pages (A5-A4, 52-105 g/m <sup>2</sup> )
Resolution	600 x 600 dpi
Zoom ratio	25-400% (FBS)
FCOT (First Copy Output Time)	10 seconds* <sup>1</sup>

### **PRINT**

Print controller	Standard: GDI, Option: PCL6/5e
Resolution	600 x 600 dpi
Operating System	Windows 98(ethernet only), 98SE, ME, NT4.0(ethernet only), 2000, XP, Server2003 (network print only)* <sup>2</sup> , Vista

### **SCAN**

Scan speed	Mono: 3.2 seconds Colour: 8.1 seconds
Scan interface	Standard: TWAIN, Option: Ethernet
Resolution	600 / 300 / 200 / 100* <sup>3</sup> dpi
Scan format	TIFF, PDF, JPEG* <sup>3</sup>
Scan to E-Mail	Standard with OB
Scan to Folder	Standard with OB
Scan to FTP	Standard with OB

### **FAX**

Modem speed	33.6 Kbps
Transmission speed	2 seconds
Memory	8 MB (650 A4 pages)* <sup>4</sup> Max.: 40 MB (3,370 A4 pages)* <sup>4</sup>
Memory backup	72 hours
Address book	200 addresses
Group Dialing	32 groups
Broadcasting	230 addresses

- A4 Max. Copy / Print size
- 19 ppm
- 10 ppm with duplex
- LED
- Platen
- 500 sheet standard paper capacity (A5-A4, 60-90 g/m<sup>2</sup>)
- 50 sheet bypass (A6-A4, 60-120 g/m<sup>2</sup>)
- Max.: 2 x 500 sheets
- Quad Access
- Standard USB interface, Option: Ethernet



#### OfficeBridge Features

- Network Printer
- Scan to Folder
- Scan to E-Mail
- Scan to FTP
- Network PC-Fax
- Fax Forwarding
- 1,000 addresses in address book
- 100 groups in group dialing
- LDAP compliance
- Workflow Management

\*<sup>1</sup> From FBS with 1st cassette selection. \*<sup>2</sup> Utilities (InfoMonitor etc) are not supported.

\*<sup>3</sup> Colour scan only. \*<sup>4</sup> Based on ITU-T Test Document 1 stored at normal resolution.



# MFX-1350 OB

## MFX-1350

### **COPY**

ADF	80 pages (A5-A4, 52-105 g/m <sup>2</sup> )
Resolution	600 x 600 dpi
Zoom ratio	25-400% (FBS)
FCOT (First Copy Output Time)	12 seconds* <sup>1</sup>

### **PRINT**

Print controller	Standard: GDI, Option: PCL6/5e
Resolution	600 x 600 dpi
Operating System	Windows 98(ethernet only), 98SE, ME, NT4.0(ethernet only), 2000, XP, Server2003 (network print only)* <sup>2</sup> , Vista

### **SCAN**

Scan speed	Mono: 3.2 seconds Colour: 8.1 seconds
Scan interface	Standard: TWAIN, Option: Ethernet
Resolution	600 / 300 / 200 / 100* <sup>3</sup> dpi
Scan format	TIFF, PDF, JPEG* <sup>3</sup>
Scan to E-Mail	Standard with OB
Scan to Folder	Standard with OB
Scan to FTP	Standard with OB

### **FAX**

Modem speed	33.6 Kbps
Transmission speed	2 seconds
Memory	8 MB (650 A4 pages)* <sup>4</sup> Max.: 40 MB (3,370 A4 pages)* <sup>4</sup>
Memory backup	72 hours
Address book	200 addresses
Group Dialing	32 groups
Broadcasting	230 addresses

- A4 Max. Copy / Print size
- 13 ppm
- 8ppm with duplex
- LED
- Platen
- 500 sheet standard paper capacity (A5-A4, 60-90 g/m<sup>2</sup>)
- 50 sheet bypass (A6-A4, 60-120 g/m<sup>2</sup>)
- Max.: 2 x 500 sheets
- Quad Access
- Standard USB interface, Option: Ethernet

**Office**  
**Bridge**

OfficeBridge Features

- Network Printer
- Scan to Folder
- Scan to E-Mail
- Scan to FTP
- Network PC-Fax
- Fax Forwarding
- 1,000 addresses in address book
- 100 groups in group dialing
- LDAP compliance
- Workflow Management

\*<sup>1</sup> From FBS with 1st cassette selection. \*<sup>2</sup> Utilities (InfoMonitor etc) are not supported.

\*<sup>3</sup> Colour scan only. \*<sup>4</sup> Based on ITU-T Test Document 1 stored at normal resolution.

# F-305



## **COPY**

ADF	80 pages (A5-A4, 52-105 g/m <sup>2</sup> )
Resolution	600 x 600 dpi
Reduction/Enlargement	25-400% (FBS)

## **PRINT**

Print controller	Standard: GDI, Option: PCL6/5e
Resolution	600 x 600 dpi
Operating System	Windows 98(ethernet only), 98SE, ME, NT4.0(ethernet only), 2000, XP, Server2003 (network print only)* <sup>2</sup> , Vista

## **SCAN**

Scan speed	Mono: 3.2 seconds
Scan interface	Standard: TWAIN, Option: Ethernet
Resolution	600 / 300 / 200 dpi
Scan format	TIFF, PDF
Internet Fax	Option

## **FAX**

Modem speed	33.6 Kbps
Transmission speed	2 seconds
Memory	8MB (650 A4 pages)* <sup>3</sup> Max.: 40 MB (3,370 A4 pages)* <sup>3</sup>
Memory backup	72 hours
Address book	200 addresses
Group Dialing	32 groups
Broadcasting	230 addresses
Internet Fax	Option

- A4 Max. Copy / Print size
- 13 ppm
- LED
- 500 sheet standard paper capacity (A5-A4, 60-90 g/m<sup>2</sup>)
- 50 sheet bypass (A6-A4, 60-120 g/m<sup>2</sup>)
- Max.: 2 x 500 sheets
- 23 sec. warm up time
- Quad Access
- Standard USB interface, Option: Ethernet

## **NETWORK CARD**

### NP400 Features

- Network Printer
- Internet Fax
- Network TWAIN Scan

\*<sup>1</sup> From FBS with 1st cassette selection. \*<sup>2</sup> Utilities (InfoMonitor etc) are not supported.

\*<sup>3</sup> Based on ITU-T Test Document 1 stored at normal resolution.



## **SX-2500CG**

Security	WEP (64/128) SSID WPA-PSK (TKIP/AES) WPA2-PSK (AES)
Configuration	Web Browser interface AdminManager
Interfaces	WLAN 802.11 b/g 10Base-T and 100Base-TX
Powerconsumption	9W (DC 5V 1,8A)
Dimensions	36 x 114 x 138 mm (without foot and aerial)



## **SX-2000WG**

Security	WEP (64/128) SSID WPA-PSK (TKIP/AES) WPA2-PSK (AES)
Configuration	Web Browser interface Quick Setup, telnet
Interfaces	WLAN 802.11 b/g 10Base-T and 100Base-TX
Powerconsumption	9W (DC 5V 1,8A)
Dimensions	36 x 140 x 143 mm (without foot and aerial)

# **WIRELESS SOLUTIONS**

- No driver required
- No additional software required
- Supports networkscanning
- Easy configuration and quick setting up with webbrowser interface
- Ethernet forwarding, individual security settings are kept active
- crossplatform and compatible with every operating system

- Convert your USB MFP to a wireless network device
- Easy wireless configuration with MS Windows Connect Now.
- With printserver functionality

# SYSTEM CONFIGURATION

- Standard
- Option

	MFX-2725	MFX-27250B	MFX-2225	MFX-22250B	MFX-2700	MFX-27000B	MFX-2200	MFX-22000B	MFX-2050	MFX-1450	MFX-1930	MFX-19300B	MFX-1330	MFX-13500B	F-305
RADF	●	●	●	●											
ADF					●	●	●	●	●	●	●	●	●	●	●
Duplex Copy	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Platen	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
33.6K Fax	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
GDI Printer	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
TWAIN-Colour Scan								●	●	●	●	●	●	●	●
TWAIN-Mono Scan	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Duplex	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Networking	○	●	○	●	○	●	○	●	●	○	●	○	●	○	○
Network PC-Fax	○	●	○	●	○	●	○	●	●	○	●	○	●	○	
Internet-Fax	○	●	○	●	○	●	○	●	●	○	●	○	●	○	
Scan to E-Mail	○	●	○	●	○	●	○	●	●	○	●	○	●	○	
Scan to Folder	○	●	○	●	○	●	○	●	●	○	●	○	●	○	
Scan to FTP								●	●	○	●	○	●		
Touch Display	●	●	●	●	●	●	●	●	●						
PCL 6/5e Print	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Fax Forwarding	○	●	○	●	○	●	○	●	●	○	●	○	●		

# CONSUMABLES

	MFX-2725	MFX-27250B	MFX-2225	MFX-22250B	MFX-2700	MFX-27000B	MFX-2200	MFX-22000B	MFX-2050	MFX-1450	MFX-1930	MFX-19300B	MFX-1330	MFX-13500B	F-305
Toner TS22	●	●	●	●	●	●	●	●							
Toner TS2030								●	●	●	●	●	●	●	
Toner TS560															●
Drum DK22	●	●	●	●	●	●	●								
Drum DK2030								●	●	●	●	●	●	●	●

Toner TS22: 20,000 pages (A4 6%)  
 Toner TS2030: 16,000 pages (A4 6%)  
 Toner TS560: 15,000 pages (A4 4%)

Drum DK22: 100,000 pages  
 Drum DK2030: 30,000 pages  
 (F-305: 20,000 pages)



**MURATEC EUROPE GmbH**

Hanns-Martin-Schleyer-Str. 3  
47877 Willich, GERMANY

**[www.muratec-europe.de](http://www.muratec-europe.de)**

**MURATEC EUROPE (UK)**

343 Edinburgh Avenue, Slough  
Berkshire, SL1 4TU, UK

**[www.muratec-europe.co.uk](http://www.muratec-europe.co.uk)**